



140HWS

KERNOW PRINT®

DRY TONER

Inside Out Film

- Printable adhesive construction for window signage
- Printable on the paper side
- The lightly textured, paper face enables a vibrant image
- Apply inside by removing the strippable border, which reveals a clear adhesive liner, and allows for the printed graphic to be viewed from outside
- Easily applied to windows with excellent repositionability & removability

Compatibility Guidance:

Suitable for most thermal transfer and dry toner (laser/LED/flash fusion) print processes, both mono and colour small-volume, mid-volume & production machines.

On such machines the user must establish for themselves the optimum settings and paper path, being aware of the thickness and weight of the material.

Recommended Conditions:

Printroom	10°C - 30°C	40% - 55% RH
Usage	-40°C - 60°C	10% - 100% RH
Storage	10°C - 20°C	20% - 55% RH

Available in A4 sheets

Total Thickness (215µ/8.5mil) Weight (232gsm)

Kernow Coatings Ltd
Kernick Road
Penryn, Cornwall
TR10 9DQ
United Kingdom

www.kernowcoatings.com
sales@kernowcoatings.com
T: +44 (0)1326373147
F: +44 (0)1326376614

Registered in England
No. 1092182
A Member of the Sensitiser
Group of Companies

The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. We recommend users make their own assessments to satisfy themselves as to the suitability of this product for their application. Copyright Sensitiser Group 2016