



## 195HWT.6UPDH

### 6 Up Door Hanger Matt White Film

- Pre-perforated and print ready to personalise
- Matt white opaque suitable for full colour duplex printing
- Waterproof, tear-proof, greaseproof
- No need to laminate

**Please Note:** Keep all print a minimum of 4mm away from all perforations  
Fold all perforations in both directions for easy removal of pieces from the sheet

#### Compatibility Guidance:

Suitable for most thermal transfer and dry toner (laser/LED/flash fusion) print processes, both mono and colour small-volume, mid-volume & production machines.

On such machines the user must establish for themselves the optimum settings and paper path, being aware of the thickness and weight of the material.

#### Recommended Conditions:

Printroom	10°C - 30°C	40% - 55% RH
Usage	-40°C - 120°C	10% - 100% RH
Storage	10°C - 20°C	20% - 55% RH

Available in A4

Also available as 3/page in 145µ/5.7mil (145.3UPDH) and 195µ/7.7mil (195.3UPDH)

Thickness (195µ/7.7mil) Weight (260gsm)

Kernow Coatings Ltd  
Kernick Road  
Penryn, Cornwall  
TR10 9DQ  
United Kingdom

www.kernowcoatings.com  
sales@kernowcoatings.com  
T: +44 (0)1326373147  
F: +44 (0)1326376614

Registered in England  
No. 1092182  
A Member of the Sensitiser  
Group of Companies

