

# Opaline Light 153 153SBB

## Budget Matt Backlight Polyester Film

### Applications

- Lightboxes
- Backlit applications indoor and outdoor

### Benefits

- Cost effective matt backlit material for front print
- Optimum day/night performance
- Fast dry for improved workflow
- Weather resistant for outdoor displays
- Antistatic treatment avoids attracting dust and slipping in the printer

### Post Printing Information for Latex & Solvent Inks:

As with all filmic media, this product must be allowed to “gas-out” after printing.

This can be achieved by leaving the prints face up, ideally 24 hours, to set and harden the unique scratch resistant properties.

If unable to do this e.g. with a long print run, after printing the roll stand it vertically and loosely unwind as much as possible, to allow air in and gases out.


### Printability:



### Thickness:



### Available widths:



### Recommended Conditions:

Printroom	15°C - 30°C	30% - 65% RH
Usage	-40°C - 80°C	10% - 90% RH
Storage	10°C - 20°C	20% - 50% RH



KERNOW COATINGS | Kernick Road | Penryn | Cornwall | TR10 9DQ | UK

[www.kernowcoatings.com](http://www.kernowcoatings.com) | [sales@kernowcoatings.com](mailto:sales@kernowcoatings.com) | T: +44 (0)1326373147

Registered in England | No. 1092182 | A Member of the Sensitisers Group of Companies