

Opaline Frost 195 195HHF

Backlit Polyester Film

Applications

- Lightboxes
- Backlit applications indoor and outdoor
- Frosted binder covers and menu or wine list inserts

Benefits

- Double diffusion backlight film, printable both sides
- Ideal combination of whiteness and translucency
- Optimum day/night performance
- Scratch and weather resistant for outdoor applications and scrolling displays
- Antistatic treatment avoids attracting dust and slipping in the printer

Post Printing Information for Latex & Solvent Inks:

As with all filmic media, this product must be allowed to “gas-out” after printing.

This can be achieved by leaving the prints face up, ideally 24 hours, to set and harden the unique scratch resistant properties.

If unable to do this e.g. with a long print run, after printing the roll stand it vertically and loosely unwind as much as possible, to allow air in and gases out.

Recommended Conditions:

Printroom	15°C - 30°C	30% - 65% RH
Usage	-40°C - 80°C	10% - 90% RH
Storage	10°C - 20°C	20% - 50% RH



KERNOW COATINGS | Kernick Road | Penryn | Cornwall | TR10 9DQ | UK

www.kernowcoatings.com | sales@kernowcoatings.com | T: +44 (0)1326373147

Registered in England | No. 1092182 | A Member of the Sensitisers Group of Companies




Printability:



Thickness:



Available widths:



* from 3rd Gen HP or later