



Classic Matt 290 290SML

Matt Lightblock Pop-Up Polyester Film

Applications

- Pop-up displays

Benefits

- Premium roll-up material - grey back, 98% opacity
- Anti-reflective, matt, bright-white front surface
- Optimum ink adhesion, fast drying
- Scratch and water resistant
- Antistatic treatment avoids attracting dust
- No slipping in the printer, ideal for perfect pop-ups
- Stiff, perfect flatness

Post Printing Information for Latex & Solvent Inks:

As with all filmic media, this product must be allowed to “gas-out” after printing.

This can be achieved by leaving the prints face up, ideally 24 hours, to set and harden the unique scratch resistant properties.

If unable to do this e.g. with a long print run, after printing the roll stand it vertically and loosely unwind as much as possible, to allow air in and gases out.

Printability:



Thickness:



Available widths:



Recommended Conditions:

Printroom	15°C - 30°C	30% - 65% RH
Usage	-40°C - 80°C	10% - 90% RH
Storage	10°C - 20°C	20% - 50% RH



KERNOW COATINGS | Kernick Road | Penryn | Cornwall | TR10 9DQ | UK

www.kernowcoatings.com | sales@kernowcoatings.com | T: +44 (0)1326373147

Registered in England | No. 1092182 | A Member of the Sensitiser Group of Companies