

Double Matt Drafting Film 050DDD

Double Matt 050DDD is a translucent polyester drafting film for manual drawing applications.

Property	Typical Value	Unit	Test Method
Total Thickness	89 +/- 4	μ	Electronic micrometer
Weight	127 +/- 4	g/m ²	Internal method

- Rapid ink drying
- Erases repeatedly with no ghosting
- Takes all plastic leads
- Antistatic surface won't attract dust
- Solvent resistant
- Litho/Screen/UVC printable, backlight applications!

Compatibility Guidance

Offset	Screen	UV/Flexo	UV Inkjet	Pen Plotting	Drafting	PPC/Laser
✓✓✓★	✓✓✓	x	✓✓	✓✓	✓✓✓	x
★ Requires Fully Oxidising Inks						

Recommended Conditions

Printroom	15°C - 30°C	30% - 65% RH
Usage	-40°C - 100°C	10% - 80% RH
Storage	10°C - 20°C	20% - 50% RH

Please return unused product to its original packaging

Shelf Life: 24 months after delivery (under recommended storage conditions)

Kernow Coatings Ltd
Kernick Road
Penryn, Cornwall
TR10 9DQ
United Kingdom

www.kernowcoatings.com
sales@kernowcoatings.com
T: +44 (0)1326373147
F: +44 (0)1326376614

Registered in England
No. 1092182
A Member of the Sensitiser
Group of Companies