

# KernowLoft 125PLD

KernowLoft 125PLD is a translucent, double matt pen plotting film for CAD applications.

Property	Typical Value	Unit	Test Method
Total Thickness	141 +/-2	μ	Electronic micrometer
Weight	201+/-2	g/m <sup>2</sup>	Internal method

- Specially designed for flatbed plotters and **guaranteed** to lay flat in use
- Will accept pressure fed ball pens in addition to standard plotting or manual inks
- Litho/Screen/UVC printable, Backlight applications

## Compatibility Guidance

Offset	Screen	UV/Flexo	UV Inkjet	Pen Plotting	Drafting	PPC/Laser
✓✓✓★	✓✓✓	✓✓✓	✓✓✓	✓✓✓	x	x
★ Requires Fully Oxidising Inks						

## Recommended Conditions

Printroom	15°C - 30°C	30% - 65% RH
Usage	-40°C - 100°C	10% - 80% RH
Storage	10°C - 20°C	20% - 50% RH

Please return unused product to its original packaging

Shelf Life: 24 months after delivery (under recommended storage conditions)

Kernow Coatings Ltd  
Kernick Road  
Penryn, Cornwall  
TR10 9DQ  
United Kingdom

www.kernowcoatings.com  
sales@kernowcoatings.com  
T: +44 (0)1326373147  
F: +44 (0)1326376614

Registered in England  
No. 1092182  
A Member of the Sensitiser  
Group of Companies