

FLOORSHARK™ FOR DRY TONER

FloorShark™ is the only dry toner floor graphic rigorously tested and certified for slip resistance with a unique shark-skin coating. It's perfect for indoor environments, and can be applied to all smooth and hard floors, including low pile carpet tiles. Unlike other floor graphics, FloorShark™ doesn't shrink and there's no risk of the edge peeling or gumming up. Better yet, it's easy to remove – all in one piece and no residue.

WHY CHOOSE US?

Not only is FloorShark™ Dry Toner perfect for directing the flow of store traffic and reminding customers of social distancing, you can also take advantage of instant advertising – right on the floor. Customize floor graphics with your logo or sale items to keep customers “on-top” of your brand. A perfect combination for safe and reliable graphics that are easy to print and apply.

FEATURES

- Unique sharkskin coating – R10 certified
- Great printability – fast drying
- No need to laminate – print & apply
- No shrinkage & no dirty edges
- Resists heavy foot traffic – from heels to trucks
- Bfl-s1 and EN 13501 fire ratings



UK, EU, ROW PRODUCT LIST

PRODUCT DESCRIPTION	SIZES	PRODUCT CODE
300µ KernowPrint (PET) FloorShark™ for Dry Toner	SRA3	160HTFG
300µ KernowPrint (PET) FloorShark™ for Dry Toner	A4 ø 205mm circle	160HTFG.1C.A4
300µ KernowPrint (PET) FloorShark™ for Dry Toner	SRA3 ø 315mm circle	160HTFG.1C.SRA3

US PRODUCT LIST

PRODUCT DESCRIPTION	SIZES	PRODUCT CODE
7.1 mil KernowPrint (PET) FloorShark™ for Dry Toner	SRA3	P46
7.1 mil KernowPrint (PET) FloorShark™ for Dry Toner	8.5x11 ø 6.8in circle	P460

*for the size/pack-specific codes, please refer to our Narrow Format Product Guide



KERNOWPRINT®
DRY TONER

KERNOWPRINT (PET) FLOORSHARK™ FOR DRY TONER

Easy To Print, Simple To Apply



DRY TONER FRIENDLY

"Thanks to FloorShark™ for Dry Toner, we didn't need a large wide format printer to be able to print floor graphics!"

Overall Toughness: ★★★★★

Outdoor Use: N/A

Heat Resistance: ★★★★★

Chemical Resistance: ★★★

Rigidity: ★★★

Compatibility:

Laser/Dry Toner: ★★★★★

Adhesive: Removable solvent

KERNOWPRINT (PET) FLOORSHARK™ FOR DRY TONER
CERTIFICATIONS

TESTED ON

KEY FEATURES

- Matt white opaque sheet, suitable for full colour duplex printing
- Waterproof, tearproof, greaseproof, can be hole punched
- Ideal for documents where strength and light weight are required
- No need to laminate

IDEALLY SUITED FOR

- Indoor floor graphic for social distancing
- Supermarkets, shopping malls & retail outlets
- Use for directional or guiding floor signage
- Convention centers, schools, colleges & airports

TECHNICAL DATA

	Typical Value	Units
Property	160HTFG/P46	
Total Thickness	300/11.8	µ/mil
Total Weight	346	gsm
Face Film Thickness (no adhesive)	153	µ/mil
Face Film Weight (no adhesive)	190	gsm
Liner Thickness	120	µ/mil
Liner Weight	130	gsm
Adhesive Peel on Stainless Steel	8.5	N/25mm
Adhesive Application Temperature	5 to 50 / 41 to 122	°C/°F
Adhesive Service Temperature	-40 to 180 / -40 to 356	°C/°F

RECOMMENDED CONDITIONS:

Printroom	10°C - 30°C (50°F - 86°F)	40% - 55% RH
Storage	10°C - 20°C (50°F - 68°F)	20% - 55% RH

Please return unused product to its original packaging.
Shelf Life: 24 months after delivery (under recommended storage conditions).

The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted.
We recommend users make their own assessments to satisfy themselves as to the suitability of this product for their application. Regional certification differences apply.