

KERNOWJET FLOORSHARK™

KernowJet FloorSharK™ is a unique floor graphics solution for indoor applications. It's perfect for retail stores, supermarkets & shopping centres, airports, travel hubs, convention centres, ideal for all smooth hard floors from concrete to tiling, also including low pile carpets tiles. Its unique sharkskin coating absorbs the inks and dries to a hard slip-resistant surface. The coating offers a high R10-certified slip resistance, Bfl-s1 and EN 13501 fire ratings and eliminates the need to laminate.



WHY CHOOSE US?

The floor graphics film is PVC-free and strongly tear-resistant, it will withstand everything from pallet trucks to stiletto heels. With its specifically developed adhesive, it is easy to apply and to reposition while applying - it will definitely not stretch or become distorted.

KernowJet FloorSharK™ offers an excellent removability; it is ideal for smaller designs like stickers as well as covering of bigger surfaces made of multiple film strips. With zero shrinkage - avoiding the risk of a rim of dirty adhesive forming around the print once applied. FloorSharK™ can be applied with either a butt joint or with an overlapping technique.

FEATURES

- Ultra-tough floor graphic, suitable for smooth indoor floors
- Unique sharkskin coating absorbs the ink & dries tough, no need to laminate
- Easy to apply & easy to remove, does not tear into small pieces when removing
- No shrinkage - no risk of a rim of dirty adhesive forming around the print
- Bfl-s1 and EN 13501 fire ratings

UK, EU AND ROW PRODUCT LIST

PRODUCT DESCRIPTION	WIDTH	LENGTH	PRODUCT CODE
265µ KernowJet FloorSharK™ (PET) 170TFG	1372mm	25m	170TFG

US PRODUCT LIST

PRODUCT DESCRIPTION	WIDTH	LENGTH	PRODUCT CODE	
10.4mil KernowJet FloorSharK™ (PET) 170TFG	54"	60"*	100'	170TFG



KERNOWJET®
LATEX, SOLVENT & UV

KERNOWJET FLOORSHARK™

EASY TO PRINT, SIMPLE TO APPLY



EXPAND YOUR MARKETING

"For decades skyscrapers & billboards have been used for marketing, why not utilise the floor as well. Consumers awareness for the space around them is heightened after COVID, utilising the floor is the next step."

MACHINE COMPATIBILITY:

Latex: ★★★★★

(Eco)Solvent: ★★★★★

UV: ★★★★★

KERNOWJET FLOORSHARK™



KEY FEATURES

- Unique sharkskin coating, ink absorbent & drying tough and no lamination required
- R10 slip certified, Bfl-s1 and EN 13501 fire ratings
- Durable surface, resists pallet truck scuffing & stiletto heels
- Also perfect for application to short-pile carpet tiles
- Easy to apply & easy to remove

IDEALLY SUITED FOR

- Smooth hard floors
- Low pile carpet tiles
- Indoor floorgraphic displays: airports, convention centres, supermarkets

TECHNICAL DATA

	Typical Value	Units
Property	170TFG	
Total Thickness	265 +/- 6 10.4 +/- 0.2	µ/mil
Total Weight	310 +/- 8	gsm
Face Film Thickness (no adhesive)	170 +/- 4 6.7 +/- 0.2	µ/mil
Face Film Weight (no adhesive)	224 +/- 5	gsm
Adhesive thickness	35 +/- 5 1.4 +/- 0.2	µ/mil
180° Peel Adhesion (SS)	1100 +/- 100	SS gF
Adhesive Service Temperature	-40 to +180	°C/ °F
Liner Thickness	65 +/- 3 2.6 +/- 0.1	µ/mil
Liner Weight	83 +/- 2	gsm
Recommended conditions:		
Printroom	15°C - 30°C (59°F - 86°F)	30% - 65% RH
Storage	10°C - 20°C (50°F - 68°F)	20% - 50% RH

The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. We recommend users make their own assessments to satisfy themselves as to the suitability of this product for their application. Regional certification differences apply.