

KERNOWJET WALLSHARK®

KernowJet WallSharK is a PVC-free, highly tear-resistant, self-adhesive film. It is printable with all standard Wide-Format inks offering a wide color gamut. The textured 'sharkskin' top coating of this unique wall graphic solution absorbs the ink which then hardens into a very tough, scratch-resistant surface. KernowJet WallSharK is suitable for indoor application on smooth walls.



WHY CHOOSE US?

It is manufactured on an ultra-strong thick polyester base, which will enable the applicator to handle WallSharK easily and reposition it while applying, without any distortion.

As it is absolutely shrink-free it is the perfect substrate for easy, seamless butt joint application. KernowJet WallSharK comes with a removable adhesive. We have designed it to have a good adhesion to most walls. For short-term applications applied to a wide range of wall surfaces, display substrates and paints, the removability must be tested before application, in an area out of sight (patch test).

Hard-wearing and durable, it is the perfect solution for environmentally-conscious customers. It is ideal for POS, museums, hotels, restaurants and much more.

FEATURES

- Easy application, no stretching or distortion
- Unique sharkskin coating absorbs the ink & dries tough, no need to laminate
- Easy to apply & easy to remove, does not tear into small pieces when removing
- Highly scratch-resistant - washable with a soft cloth and soapy water
- PVC Free & scratch resistant.

UK EU PRODUCT LIST

PRODUCT DESCRIPTION	WIDTH	LENGTH	PRODUCT CODE
265µ KernowJet WallSharK® (PET) 170TWG	1372mm	25m	170TWG
	1524mm		

US PRODUCT LIST

PRODUCT DESCRIPTION	WIDTH	LENGTH	PRODUCT CODE
10.4mil KernowJet Wall SharK® (PET) 170TWG	54" 60"*	100'	170TWG

*custom - denotes custom only product - please ask your representative for details



KERNOW
COATINGS

KERNOWJET®
LATEX, SOLVENT & UV

KERNOWJET WALLSHARK®

Easy to Print, Simple to Apply



TIME SAVING SHARKSKIN

"The best selling floor graphic material now available for use on your walls. Advertise on your floors and walls using the same material & saving time."

Machine Compatibility:

Latex: ★★ ★

(Eco)Solvent: ★★ ★

UV: ★★ ★

KernowJet Wallshark

Certified for
HP Latex Inks



KEY FEATURES

- Unique sharkskin coating, ink absorbent & drying tough and no lamination required
- PVC & Scratch resistant
- Easy to apply & easy to remove

IDEALLY SUITED FOR

- PoS & PoP
- Museums, hotels and
- Short term displays

	Typical Value	Units
Property	170TWG	
Total Thickness	265 +/- 6 10.4 +/- 0.2	µ/mil
Total Weight	310 +/- 8	gsm
Face Film Thickness (no adhesive)	170 +/- 4 6.7 +/- 0.2	µ/mil
Face Film Weight (no adhesive)	224 +/- 5	gsm
Adhesive thickness	35 +/- 5 1.4 +/- 0.2	µ/mil
180° Peel Adhesion (SS)	1100 +/- 100	SS gF
Adhesive Service Temperature	-40 to +180	°C/ °F
Liner Thickness	65 +/- 3 2.6 +/- 0.1	µ/mil
Liner Weight	83 +/- 2	gsm

RECOMMENDED CONDITIONS:

Printroom	15°C - 30°C (59°F - 86°F)	30% - 65% RH
Storage	10°C - 20°C (50°F - 68°F)	20% - 50% RH

The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. We recommend users make their own assessments to satisfy themselves as to the suitability of this product for their application. Regional certification differences apply.